

Enphase® M215



The **Enphase Energy Microinverter System** improves energy harvest, increases reliability, and dramatically simplifies design, installation, and management of solar power systems.

The Enphase System includes the microinverter, the Envoy Communications Gateway,[™] and Enlighten,[®] Enphase's monitoring and analysis software.

PRODUCTIVE

- Maximises energy production
- Minimises impact of shading, dust, and debris
- System availability greater than 99.8%

RELIABLE

- 4th-generation product
- More than one million hours of testing and five million units shipped

SMART

- Quick and simple design, installation, and management
- 24/7 monitoring and analysis

SAFE

- Extra low-voltage DC reduces fire risk
- No single point of system failure
- Easy installation with Engage Cable

INPUT DATA (DC)	M215-60-230-S22-E
Recommended input power (STC)	190 - 270 W
Maximum input DC voltage	48 V
Peak power tracking voltage	27 V - 39 V
Operating range	16 V - 48 V
Min/Max start voltage	22 V / 48 V
Max. DC short circuit current	15 A

OUTPUT DATA (AC)	
Peak output power	225 W
Rated output power	215 W
Rated output current	0.94 A
Nominal voltage	230 V
Nominal frequency	50.0 Hz
Power factor	>0.95
Maximum units per 20 A branch circuit	17 (Ph + N), 51 (3Ph + N)
Maximum units per cable section	17 (Ph + N), 27 (3Ph + N)

EFFICIENCY	
EN 50530 (EU) efficiency	95.7%
Static MPPT efficiency (weighted, reference EN50530)	99.6%
Dynamic MPPT efficiency (fast irradiation changes, reference EN50530)	99.3%
Night time power consumption	0.055 W

MECHANICAL DATA	
External operating temperature range (ambient)	-40°C to +65°C
Internal operating temperature range	-40°C to +85°C
Enclosure environmental rating	Outdoor - IP67
Connector type	MC4
Dimensions (WxHxD)	179 mm x 217 mm x 28 mm (with bracket)
Weight	1.66 kg
Cooling	Natural convection - No fans

FEATURES	
Compatibility	60-cell PV modules
Communication	Power line
Monitoring	Enlighten Manager and MyEnlighten monitoring options
Transformer design	High frequency transformers, galvanically isolated
Compliance	AS4777, C10/11, CEI_0-21, EN50438, EN62109-1, EN62109-2, ERDF-NOI-RES_13E_V5, G59/2, G83/2, VDE-0126-1-1 + A1, VDE AR-N 4105

To learn more about Enphase microinverter technology, visit enphase.com/au.